



# Thermia Comfort Optimum



Comfort Optimum

Thermia Comfort Optimum

(SPF)\*


70%,

TWS\*\*,

Comfort.

100

Thermia Online,



Eco-design Directive 811/2013



# Comfort Optimum

- 1 ( ), 28 Cu
- 2 ( ), 28 Cu
- 3 - , 22 Cu: 6-8 kW, 28 Cu: 10-17 kW
- 4 - , 22 Cu: 6-8 kW, 28 Cu: 10-17 kW
- 5 , 22 Cu
- 6 , 22 Cu
- 7 , 22 Cu
- 8



Comfort Optimum		4	6	8	10
		R407C	R407C	R407C	R407C
	kg	0.75	1.2	1.35	1.45
		Scroll	Scroll	Scroll	Scroll
<b>3-N</b>	Volt	400	400	400	400
	kW	2.3	3.0	3.2	4.2
	kW	0.1	0.1	0.1	0.3
	kW	3/6/9	3/6/9	3/6/9	3/6/9
	A	15	9	10	12
	A	16 <sup>4</sup> /20 <sup>5</sup> /25 <sup>6</sup>	10 <sup>4</sup> /16 <sup>5</sup> /20 <sup>6</sup>	10 <sup>4</sup> /16 <sup>5</sup> /20 <sup>6</sup>	16 <sup>4</sup> /16 <sup>5</sup> /20 <sup>6</sup>
	COP <sup>2</sup>	4.58	4.74	4.88	4.84
	COP <sup>3</sup>	4.09	4.04	4.34	4.24
	kW	4.09	5.33	7.51	9.40
	kW	1.0	1.3	1.7	2.2
<b>Max/Min</b>	°C	20/-10	20/-10	20/-10	20/-10
	°C	60/20	60/20	60/20	60/20
		+ -17°C ± 2			
	dB(A)	42	47	44	46
		180	180	180	180
	kg	225	229	229	229
	kg	405	409	409	409

\* SPF = ( )

\*\* TWS =

Thermia.

- 1) IEC61000.
- 2) At B0W35 10K ( , ).
- 3) At B0W35 EN 14511 ( , ).
- 4) 3 kW
- 5) 6 kW
- 6) 9 kW

7)

8)

EN ISO 3741 BOW45 (EN 12102).